

Tapered Buttons Bits for Small Hole Drilling

Email: sales@superdrill.com.cn

Website: <http://www.hbsuperdrill.com>

Code No.	Diameter(mm)	Length (mm)	Carbide Dimension	Code No.	Diameter(mm)	Length (mm)	Carbide Dimension
Q4-26-722-65	26	65	0710×4	Q7-38-722-50	38	50	0710×2
Q4-28-722-55	28	55	0710×4				0913×5
Q4-28-722-80	28	80	0710×4	Q7-38-722-60	38	60	0710×2
Q6-28-722-71	28	71	0710×4				0913×5
			0610×2	Q7-38-722-71	38	71	0710×2
Q6-28-722-80	28	80	0710×4				0913×5
			0610×2	Q7-38-722-80	38	80	0710×2
Q6-30-722-65	30	65	0710×6				0913×5
Q5-30-722-65	30	65	0710×5	Q8-38-722-50	38	50	0710×2
Q5-32-722-60	32	60	0711×2				0812×6
			0812×3	Q8-38-722-80	38	80	0710×2
Q6-32-722-60	32	60	0711×6				0812×6
Q7-32-722-50	32	50	0710×7	Q6-40-722-60	40	60	0812×2
Q7-32-722-55	32	55	0710×7				0913×4
Q7-32-722-60	32	60	0710×7	Q7-40-722-50	40	50	0812×2
Q7-32-722-71	32	71	0710×7				0913×5
Q7-32-722-80	32	80	0710×7	Q7-40-722-60	40	60	0812×2
Q8-32-722-71	32	71	0710×8				0913×5
Q9-32-722-55	32	55	0710×9	Q7-40-722-71	40	71	0812×2
Q7-33-722-55	33	55	0710×7				0913×5
Q7-33-722-80	33	80	0710×7	Q7-40-722-80	40	80	0812×2
Q8-33-722-80	33	80	0710×8				0913×5
Q9-33-722-71	33	71	0710×8	Q8-40-722-60	40	60	0812×2
Q6-34-722-60	34	60	0710×6				0913×6
Q7-34-722-60	34	60	0710×7	Q7-41-722-50	41	50	0812×2
Q8-34-722-60	34	60	0710×8				0913×5
Q8-34-722-71	34	71	0710×8	Q7-41-722-80	41	80	0812×2
Q8-34-722-80	34	80	0710×8				0913×5
Q9-34-722-71	34	71	0710×9	Q6-42-722-50	42	50	0812×2
Q7-35-722-50	35	50	0710×2				0913×4
			0812×5	Q7-42-722-50	42	50	0812×2
Q7-35-722-60	35	60	0710×7				0913×5
Q7-35-722-80	35	80	0710×7	Q9-45-722-71	45	71	0812×3
Q8-35-722-60	35	60	0710×8				0913×6
Q8-35-722-80	35	80	0710×2	Q9-48-722-71	48	71	0812×3
	35	80	0812×6				0913×6
Q5-36-722-60	36	60	0812×5	Q7-50-722-71	50	71	1014×7
Q6-36-722-60	36	60	0812×6	Q9-51-722-80	51	80	0812×3
Q7-36-722-50	36	50	0710×2				0913×6
			0812×5	Q7-55-722-71	55	71	0913×2
Q7-36-722-60	36	60	0812×7				1014×5
Q7-36-722-80	36	80	0812×7	Q9-64-722-80	64	80	1014×3
Q5-38-722-60	38	60	0812×5				1115×6
Q6-38-722-60	38	60	0812×6				

Remarks: Other specifications are available according to customers' requirements